

VISO SPEAKER SPECIFICATIONS

	VISO LR5 Compact Monitor	VISO C20 Centre	VISO S10 Subwoofer
FREQUENCY RESPONSE (Anechoic)			
On Axis @ 0° ± 3dB	75-23,000Hz	75-23,000Hz	36-150Hz
Off Axis @ 30° ± 1.5dB	80-10,000Hz	80-10,000Hz	
LF cutoff - 10dB	65Hz	65Hz	32Hz
AMPLIFIER POWER			
Continuous			110 Watts
Dynamic			140 Watts
Dynamic Peak			280 Watts
Type			Class AB Discrete MOSFET Output Devices
SENSITIVITY (1W (2.83V) @ 1m, IEC-filtered Pink Noise, C-weighted)			
Anechoic Chamber	84dB	87dB	
Typical Listening Room	86dB	89dB	
IMPEDANCE			
Nominal	8 Ohms	8 Ohms	
Minimum	6 Ohms	6 Ohms	
INPUT POWER (RMS, Clipping < 10% Time)			
Recommended	15-80 Watts	15-80 Watts	
Program	60 Watts	60 Watts	
ACOUSTIC DESIGN			
Tweeter (Nominal)	1" (25mm) Aluminum Dome with Ferrofluid	1" (25mm) Aluminum Dome with Ferrofluid	
Woofer (Nominal)	4" (102mm) Injection Molded Metalized Polypropylene cone Rubber surround	2 x 4" (102mm) Injection Molded Metalized Polypropylene cone Rubber surround	8" (203mm) Injection Molded Metalized Polypropylene cone Rubber surround
Crossover	3,000Hz, B3	3,000Hz, B3	Fixed
Internal Volume	0.10 cu ft (2.8 liters)	0.15 cu ft (4.3 liters)	0.68 cu ft (19.3 liters)
Design Type	Bass Reflex 1" (25mm) Rear Port	Sealed	Bass Reflex 2 1/2" (64mm) Down Firing Port
SIZE (W x H x D)			
	5" x 8" x 7" 129mm x 205mm x 178mm	13 3/4" x 5 1/4" x 7" 350mm x 134mm x 178mm	9 5/8" x 14 3/4" x 15 1/2" 244mm x 375mm x 395mm
WEIGHT			
Net	5.3lb (2.4kg)/each	8.7lb (4.0kg)/each	22.8lb (10.4kg)/each
Shipping		42lb (19kg)/system	
VISO TWENTY		25lb (11kg)/system	
VISO THIRTY			
FINISH			
	High Gloss Black	High Gloss Black	Textured Black Sleeve with High Gloss Black Baffle
FEATURES			
	Gold-plated Binding Post ABS Grille Rubber Bumpers	Gold-plated Binding Post ABS Grille Rubber Bumpers	Phase Switch 10dB Volume Switch On-Standby/Off Gold-plated RCA

All specifications are subject to change without notice. NAD® is a trademark of Lenbrook Corp., used under licence by NAD Electronics®, a division of Lenbrook Industries Limited. ©2009 NAD Electronics. All rights reserved.